




# **TUSKBOND V15** Vinyl Adhesive



# **PRODUCT DESCRIPTION:**

Tuskbond V15 Vinyl Adhesive is a sprayable acrylic aerosol adhesive which has a variety of uses including fixing vinyl sheets and floor coverings. It has a synthetic polymer solution blended with a suitable LPG propellant to give an easy spray aerosol.

### STORAGE:

Protect from extremes of temperature in a controlled environment between 15 and 35°C, and away from direct sunlight. Do not stand on a cold concrete floor. Low temperatures can result in irreparable separation of the adhesive. Stored under the correct conditions, in original, unopened containers, the product will have a shelf life of 12 months.

DO NOT ALLOW THE PRODUCT TO FREEZE

# **DIRECTIONS FOR USE:**

- Shake well before use.
- Surfaces should be clean, dry and free from grease.
- Spray adhesive from 6" 8" away onto one or both surfaces.
- For one-way application let adhesive dry for 30 seconds until tacky, and then press into position.
- For two-way application, spray both surfaces and allow to dry for 2 – 5 minutes before bonding.

- For temporary bonding, spray one surface and allow to dry for 2 – 5 minutes before bonding.
- To prevent spray nozzle from blocking, at the end of each period of use, turn the can upside down and press nozzle until spray is clear of adhesive.
- Excess adhesive can be removed with a solvent cleaner or white spirit.

#### DISCLAIMER

All the information in the Data Sheet is based on practical experience and is published in good faith. However, because we have no control over the manner or conditions in which our products are used, or over work undertaken or end product manufactured by the purchaser, we cannot accept liability for results. Responsibility for ascertaining the suitability of products for his purposes rests with the purchaser. All conditions, representations, statements, warranties or guarantees whatsoever, whether express, implied or statutory, in respect of any goods manufactured, sold or supplied by us are hereby expressly excluded and we accept no liability in respect of any claim for damage or consequential loss caused to any property arising directly or indirectly out of the use of our products or goods.

# WWW.TUSKBOND.UK

# **FEATURES**:

TECHNICAL DATA SHEET

•UNIFORM SPRAY •FAST EASY APPLICATION •FAST DRYING •LONG OPEN TIME •BONDS A WIDE VARIETY OF SUBSTRATES

