

ACOUSTIC SILVER

Underlay Technical Specification

Item Code: TAACOUSTICSILVER

Issue Date: 12/12/2025

Issue No. 1

Natural Sponge Rubber

Suitable for the floating installation of laminate and solid timber floors

Suitable for underfloor heating. We do not recommend an underlay is used with an electric mat (or dry) underfloor heating system



Standard Specifications*

Nominal density	810 kg/m ³	
Nominal square weight	2400 g/m ² (± 200 g)	
Nominal roll weight	24 kg	
Nominal roll area	10.00m ² (1.00m x 10.00m) (± 0.05m)*	
Nominal thickness	3.00mm (± 0.2mm)	ISO 1765

BS 5808: 1991 / EN14499 : 2015

End Use Classification	GD/U, General Domestic Use
------------------------	----------------------------

Other Specifications

Odour	No objectionable odour	
Colour / backing	Gold / Silver foil	
Packaging	Clear film / Printed insert	
Thermal resistance	0.55 togs	BS 4745
Impact sound reduction (Delta Lw)	23 dB	BSEN ISO 140-8: 1998 and BSEN ISO 717-2: 1997
Emissions (US Carpet & Rug Institute)	Meets low VOC emission criteria	US Carpet & Rug Institute

Product Contents

Natural Rubber	35%	
High quality calcium carbonate	34%	
Foaming agent	5%	
Industrial butter	8%	
Other auxiliary material accelerators	18%	

Certification



Guarantee

Guaranteed for the serviceable lifetime of the carpet when used in accordance with the End Use Classification.

Notes

* The nominal roll dimensions have been quoted. These may vary slightly but will comply with the requirements of BS EN 14499:2015

THIS PRODUCT IS PRODUCED IN A FACILITY ACCREDITED TO ISO 9001, 14001 & 45001

interfloor

Interfloor Ltd., Broadway, Haslingden, Rossendale, Lancashire, BB4 4LS.
Tel: +44(0)1706 213131 Fax: +44(0)1706 214737 Web: www.interfloor.com
International Enquiries: Telephone: +44(0)1706 238825 Fax: +44(0)1706 225114